

接线盒系列-铸铝接线盒

Box-Aluminum box

产品与服务 Products and services



- 可提供增安型和本安型防爆接线箱
- 可提供防爆空机箱
- 通过防爆权威机构PTE证书和中国国家级防爆证书
- Increased safety and intrinsically safety explosion-proof junction box
- It can provide the explosion-air proof box
- Passed explosion-proof authority PTE certificate and national explosion-proof certificate

标准供货范围:

The standard scope of supply:

防水空机箱：机箱，硅密封条，外部接地装置

防爆端子机箱：机箱，硅密封条，外部接地装置，防爆接线端子及防爆电缆接头

- Water&water-proof air chassis: chassis, silicone seal, external earthing device
- Explosion proof terminal box: chassis, silicone seal, external earthing device, explosion-proof connecting terminal and explosion proof cable connector

技术参数 Technical parameters

防爆等级 Explosion proof grade	EEx e T6(增安型) Increased safety type	抗冲击性 Impact resistance	> 7Joule EN50014
	EEx ia IIC T6(本安型) Intrinsically safe type	温度范围 Temperature range	-20°C至+80°C
	EEx e(ia) IIC T6(混合安装) A mixed installation	证书 Certificate	PTB 98 ATEX 3101U
	按需可提供温度等级T5和T4 According to the available temperature grade T5 and T4		PTB 00 ATEX 1063
材质 Material	AISI 12 DIN'725	油漆 Paint	粉末喷涂 Powder coating
保护等级 Protection grade	IP66	颜色 Color	灰 RAL7001

机箱型号 Chassis type

铸铝防水机箱 Stainless explosion-Proof box	铸铝防爆机箱 Stainless explosion-Proof box	尺寸 (mm) L×W×H
5.121208	6.121208	120×120×80
5.121208-1	6.121208-1	125×125×80
5.148006	6.148006	140×80×60
5.168008	6.168008	165×80×75
5.161611	6.161611	160×160×110
5.221408	6.221408	220×140×80
5.231208	6.231208	230×120×80
5.232011	6.232011	230×200×110
5.261611	6.261611	260×160×90
5.302016	6.302016	300×200×160
5.282311	6.282311	280×230×110
5.332311	6.332311	330×230×110
5.361609	6.361609	360×160×90
5.361208	6.361208	360×120×80
5.403111	6.402311	400×230×110
5.403113	6.403113	400×310×130
5.602313	6.602313	600×230×130