

金属电缆接头

Metal cable joint

产品与服务 Products and services



技术参数 Technical parameters

材质 Material	不锈钢 SUS304/316 Stainless steel SUS304/316
夹紧件 Clamping piece	工程塑料 Engineering plastics
O-密封圈 O - seal	丁腈橡胶 (NBR) Acrylonitrile butadiene rubber (NBR)
防护等级 Protection level	IP67-5巴 IP67-5 bar
环境温度 Environment temperature	-40℃至 100℃ 瞬间可耐热至 120℃ - 40 °C to 100 °C to 120 °C can be instantly heat

产品系列 The product series

产品编码 Product coding	螺纹规格 Thread specification	卡口范围mm Bayonet range mm	外径 AG Outside diameter AG	螺纹长度GL Thread length GL
HSM-M16	M16×1.5	4-8	16.0	10.0
HSM-M20	M20×1.5	6-12	20.0	10.0
HSM-M25	M25×1.5	10-16	25.0	13.0
HSM-M32	M32×1.5	15-22	32.0	15.0
HSM-M40	M40×1.5	21-30	40.0	17.0
HSM-M50	M50×1.5	30-38	50.0	19.0
HSM-M63	M63×1.5	37-44	63.0	23.0
HSM-M72	M72×2	42-52	72.0	25.0
HSM-M75	M75×2	42-52	75.0	25.0
HSM-M80	M80×2	55-60	80.0	25.0
HSM-M88	M88×2	65-70	88.0	25.0
HSM-M100	M100×2	75-84	100.0	30.0
HSM-P13	PG13.5	6-12	20.4	10.0
HSM-P16	PG16	8-14	22.5	10.0
HSM-P21	PG21	13-18	28.3	13.0

产品编码 Product coding	螺纹规格 Thread specification	卡口范围mm Bayonet range mm	外径 AG Outside diameter AG	螺纹长度GL Thread length GL
HSM-P29	PG29	18-25	37.0	15.0
HSM-P36	PG36	22-32	47.0	19.0
HSM-P42	PG42	30-38	54.0	19.0
HSM-P48	PG48	37-44	59.3	25.0
HSM-G3/8	G 3/8	4-8	16.7	10.0
HSM-G1/2	G 1/2	6-12	21.0	13.0
HSM-G3/4	G 3/4	13-18	26.4	15.0
HSM-G1	G 1	18-25	33.2	17.0
HSM-G1 1/4	G 1 1/4	22-32	41.9	19.0
HSM-G1 1/2	G 1 1/2	30-38	47.8	19.0
HSM-G2	G 2	37-44	59.6	25.0
HSM-G2 1/2	G 2 1/2	42-52	75.1	25.0
HSM-G3	G 3	55-56	87.8	25.0
HSM-G3 1/2	G 3 1/2	65-70	100.0	25.0
HSM-G4	G4	75-84	113.0	30

地 址：上海市松江区文涵路99弄5号 201600
电 话 (Tel)：021-57744228
传 真 (Fax)：021-67742827

热 线 (Mobile)：13611696915 / 18602122391
E-Mail：GongMing784@163.com
网 址 (Web)：http://www.ritocn.com